

IN THE ABSTRACT:

On page 10 of the English Language translation of the specification, please amend the Abstract of the specification to appear as follows:

A constant velocity joint ~~in the form of a counter track twin ball joint~~, having the following characteristics: ~~[[,]] an outer joint part 12 which comprises a first longitudinal axis as well as an attaching end and an aperture end positioned axially opposite one another, and which comprises with outer ball tracks 22, an inner joint part which comprises a second longitudinal axis and attaching means for a shaft pointing towards the aperture end of the outer joint part 12, and which comprises with inner ball tracks 23, the outer ball tracks 22 and the inner ball tracks 23 form pairs of tracks 22, 23 with one another which each accommodate balls,~~ circumferentially ~~Circumferentially~~ adjoining pairs of tracks 22₁, 23₁, comprise ~~centre~~ center lines of the outer and inner ball tracks which, when the longitudinal axes are aligned, are positioned in planes which extend parallel relative to one another and are symmetric relative to the longitudinal axes~~[[,]]~~. ~~a~~ A ball cage is positioned between the outer joint part 12 and the inner joint part and comprises circumferentially distributed cage windows which each accommodate pairs of balls of adjoining pairs of tracks positioned in parallel planes~~[[,]]~~. ~~the~~ The circumferential length of second cage windows ~~18~~ for second pairs of balls ~~14~~ is smaller than the circumferential length of first cage windows for first pairs of balls.

Figure 1